

Typical Specifications

- Model:** ADD
- Description:** Fan shall be a tube axial, direct drive, cast aluminum airfoil propeller fan.
- Certifications:** Fan shall be manufactured at an ISO 9001 certified facility. Fan shall be listed by Underwriters Laboratories(UL705) and UL listed for Canada (cUL 705).
- Construction:** The fan shall be of bolted and welded construction utilizing corrosion resistant fasteners. The steel drum shall be constructed of minimum 14 gauge steel with companion flanges on both inlet and outlet. Unit shall bear an engraved aluminum nameplate. Nameplate shall indicate design CFM and static pressure. Unit shall be shipped in ISTA certified transit tested packaging.
- Coating:** All steel fan components shall be Lorenized™ with an electrostatically applied, baked polyester powder coating. Each component shall be subject to a five stage environmentally friendly wash system, followed by a minimum 2 mil thick baked powder finish. Paint must exceed 1,000 hour salt spray under ASTM B117 test method.
- Propeller:** Propeller shall be cast aluminum airfoil design with cast aluminum hub. The blade pitch shall be factory set and locked using set screws and roll pin. The hub shall be keyed and locked to the shaft utilizing two set screws or a taper lock bushing. Propeller shall be balanced in accordance with AMCA Standard 204-05, *Balance Quality and Vibration Levels for Fans*.
- Motor:** Motor shall be heavy duty type totally enclosed with permanently lubricated sealed ball bearings and furnished at the specified voltage, phase and enclosure.
- Product:** Fan shall be the ADD as manufactured by Loren Cook Company of Springfield, Missouri.