

GEMINI Vari-Flow®

DATE: PROJECT: LOCATION:	rewested	c ŪL us	Ceiling and Wall Blowers 500-700 Series
	1" W Air Flow B		
J	Grille K		

DIMENSION DATA

DIMENSION DATA											
Model No.	Housing			Outlet		Steel Grille		Del Aluminu	Ship Wt.		
	L	W	Н	A	В	J	K	7	K		
500 GCVF	17	11-7/8	11-7/8	8	6	21	14-1/4	18-3/4	13-3/4	32	
700 GCVF	21	11-7/8	11-7/8	10-1/2	4-3/4	25	14-1/4	22-11/16	13-3/4	36	
900 GCVF	31	14-11/16	14-11/16	24-1/4	6	35-1/8	17-1/8	32-3/4	16-1/4	86	

ALL DIMENSIONS IN INCHES. WEIGHTS IN LBS.

CATALOG NUMBER DEFINITION:

GCVF - 500
Series: 500,700,900...
TYPE: GC = Ceiling & Wall (includes Grille)

STANDARD CONSTRUCTION FEATURES:

Forward curved galvanized steel fan wheels - Corrosion resistant galvanized steel fan housing - Acoustically insulated housing - Aluminum backdraft damper with solid aluminum hinge rod mounted in brass bushings - Permanently lubricated ball bearing electronically commutated Vari-Flow® motor with disconnect plug - Motor mounted speed control - Interchangeable panels with removable fasteners allows the discharge to be easily changed - Internal wiring box with disconnect receptacle - Powder-painted white steel grille.

ACCESSORIES

- 1. EXTERNAL SIGNAL SPEED CONTROL
- 2. FAN SPEED CONTROL
- 3. PRESSURE CONTROLLER
- 4. WALL CAP
- 5. EAVE ELBOW (500 ONLY)
- 6. DELUXE ALUMINUM GRIĹLE
- 7. FILTER
- 8. BRICK VENT (500 & 900)
- 9. CEILING RADIATION DAMPER (500 & 900)
- 10. HANGING VIBRATION ISOLATOR
- 11. TIME DELAY SWITCH
- 12. ROOF JACK
- 13. 8" ROUND WALL CAP WITH DAMPER (500 ONLY)
- 14. 6" AND 8" ROUND DÚCT ADAPTOR (500 ONLY)
- 15. ROOF CURB
- 16. ROOF CAP

QTY	MARK	CATALOG NUMBER (see above)	FAN INFORMATION			MOTOR INFORMATION							
			CFM	SP	RPM	HP	VOLTS	HZ	РН	TYPE	AC	RIES	

MOTOR TYPE: EC (ELECTRONICALLY COMMUTATED)