


ADD


DATE:	c UL us	Tube Axial Drum Far
PROJECT:		Cast Aluminum Propelle
LOCATION:	-	Direct Drive

DIMENSION DATA

Size	Α	В	C	Drum Ga.	Ship Wt.
12	16	15-1/2	1-1/2	14 ga.	76
16	16	19-1/2	1-1/2	14 ga.	90
20	19	23-1/2	1-1/2	14 ga.	120
24	22	27-1/2	1-1/2	12 ga.	185

ALL DIMENSIONS IN INCHES. WEIGHTS IN LBS., INCLUDING STANDARD ODP MOTOR.





STANDARD CONSTRUCTION FEATURES:

Cast aluminum propeller - Painted steel housing - Permanently lubricated ball bearing motors - Corrosion resistant fasteners.

ACCESSORIES

- 1. DISCONNECT SWITCH
- 2. INLET/OUTLET GUARD
- 3. FLOOR MOUNTING FEET
- 4. HANGING BRACKETS (V OR H)
- 5. INLET BELL
- 6 SPECIAL

QTY MARK	CATALOG NUMBER	FAN INFORMATION			MOTOR INFORMATION									
		CFM	SP	RPM	НР	VOLTS	HZ	РН	TYPE	ACCESSORIES				

MOTOR TYPE: ODP (OPEN DRIP-PROOF); 2 SP 2 SPEED; X-PRF EXPLOSION PROOF; TEFC TOTALLY ENCLOSED FAN COOLED.